

TECHNICAL DATA SHEET

PRODUCT INFORMATION

FORM	Silver/Black liquid
SPECIFIC GRAVITY	0.95 g/ml
FLASH POINT	38°C
WATER RESISTANCE:	Resistant to water when dried
CHEMICAL RESISTANCE:	Resistant to most salt solutions. Not resistant to acids, alkalis or solvents.
DRYING TIME	1-2 hours
COVERAGE	Smooth surfaces: 10 m ² /L Porous or rough: 5-8 m ² /L

DIRECTIONS FOR USE

IMPORTANT

Take great care when opening paint tin as pressure can build up - always open tin away from face. Keep away from sources of ignition - no smoking. Use only in well ventilated areas. Avoid contact with eyes. Wash splashes off skin. Keep out of reach of children. Consult MSDS before use.

PREPARATION

Surfaces should be clean, dry, and free from grease, dust and loose debris. Freshly applied bituminous surface should be allowed to weather for at least 2-3 weeks before application of the Aluminium Paint.

APPLICATION

STIR THOROUGHLY BEFORE USE. Note: The appearance of a silver film on the surface of the paint, after a short period of stirring, does not signify that the paint is thoroughly uniform. It is advisable to stir for several minutes to ensure complete dispersion. Preference should be given to mechanical stirring.

Apply by brush, spray or roller. Apply two coats, allowing the first coat to dry before application of the second. To avoid staining, it is important that the Aluminium paint is not applied too thickly. Do not brush excessively as this can cause softening of the substrate and leave a patchy finish. Do not apply under damp or humid conditions, or when rain, frost or overnight dew is threatened, before the paint is dry.

CLEANING

Tools and spillages should be cleaned with white spirit.

STORAGE

Store in manufacturer's containers in a cool, dry, well ventilated and frost-free place. Do not allow water to contaminate the Aluminium Paint.

SHELF LIFE

12 months in manufacturer's unopened containers.

PACKAGING

5L tins.