

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/6

Highways PM04 Powder Component

Revision 14

Revision date 2023-09-27

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Highways PM04 Powder Component
Other means of identification / UFI	UFI: A3FJ-MMC7-HA96-DUDV.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC3] Formulation in materials;
-------------	--

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

Further information


Intended use	This product is intended for use as in the installations, bedding or grouting of paving for highways or pavements.
--------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Repr. 1B: H360;
--------------------------------------	-----------------

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Repr. 1B: H360 - May damage fertility or the unborn child .

Highways PM04 Powder Component

Revision 14

Revision date 2023-09-27

2.2. Label elements

Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to licensed waste disposal site

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Silica Sand (<1% Respirable Quartz)		14808-60-7	238-878-4		90 - 100%	
Dicyclohexyl phthalate		84-61-7	201-545-9		0 - 0.5%	Skin Sens. 1: H317; Repr. 1B: H360; Aquatic Chronic 3: H412;
Benzoyl peroxide (Dibenzoyl peroxide)	617-008-00-0	94-36-0	202-327-6		0 - 0.5%	Org. Perox. B: H241; Eye Irrit. 2: H319; Skin Sens. 1: H317;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides. Contains peroxide - Oxidising Agent - may intensify fire.
--	--

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly
--	--

Highways PM04 Powder Component

Revision 14
Revision date 2023-09-27

6.3. Methods and material for containment and cleaning up

with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Silica Sand (<1% Respirable Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total respirable dust:

8.2. Exposure controls



8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Wear:.. Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Highways PM04 Powder Component

Revision 14
Revision date 2023-09-27

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Various
Odour	Characteristic
pH	Not applicable.
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	Not applicable.
Upper Explosive Limit	Not applicable.
Lower Explosive Limit	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Partition coefficient (n-octanol/water)	Not applicable.
Autoignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Solubility	Insoluble in water

9.2. Other information

Bulk Density	≈ 2 g/cm ³
VOC (Volatile organic compounds)	Not determined

Further information

	Further information on the physical and chemical properties is not available as the main component is an inert, non hazardous substance.
--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

	Avoid contact with: Strong bases, Strong acids.
--	---

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.4. Conditions to avoid

	Avoid sparks, flames, heat and sources of ignition.
--	---

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	May cause sensitisation by skin contact.
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met).
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met).
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	May cause harm to the unborn child. May impair fertility.
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met).
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met).
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met).

Highways PM04 Powder Component

Revision 14

Revision date 2023-09-27

11.1 Information on hazard classes

Repeated or prolonged exposure	Not classified (Based on available data, the classification criteria are not met).
--------------------------------	--

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

14.7 Maritime Transport in bulk according to IMO instruments

	The product is not classified as dangerous for carriage.
--	--

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 1 - Other means of identification / UFI. 1 - UFI No.
Text of Hazard Statements in Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction. Repr. 1B: H360 - May damage fertility or the unborn child . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Org. Perox. B: H241 - Heating may cause a fire or explosion. Eye Irrit. 2: H319 - Causes serious eye irritation.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,
--	---

Highways PM04 Powder Component

Revision 14

Revision date 2023-09-27

Further information

	storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/7

Highways PM04 Resin Solution

Revision 13

Revision date 2023-09-27

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Highways PM04 Resin Solution
Other means of identification / UFI	UFI: 4E1W-5FTQ-N99C-5WDT.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC1] Adhesives, sealants; [PROC19] Hand-mixing with intimate contact and only PPE available; [ERC3] Formulation in materials; [AC4] Stone, plaster, cement, glass and ceramic articles;
-------------	--

1.3. Details of the supplier of the safety data sheet

Company	Larsen Building Products Ltd
Address	4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom
Web	www.larsenbuildingproducts.com
Telephone	+44 (0)28 9077 4000
Fax	+44 (0)28 9077 6945
Email	l.pyper@larsenbuildingproducts.com

1.4. Emergency telephone number

Emergency telephone number	(00353) 01 809 2166
Company	National Poisons Centre of Ireland 8am-10pm 7 days a week

Further information

Intended use	This product is intended for use as in the installations, bedding or grouting of paving for highways or pavements.
--------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; STOT SE 3: H335; Repr. 2: H361d; STOT RE 1: H372; Aquatic Chronic 3: H412;
--------------------------------------	--

2.2. Label elements

Hazard pictograms	
Signal Word	Danger

Highways PM04 Resin Solution

Revision 13
Revision date 2023-09-27

2.2. Label elements

Hazard Statement	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Repr. 2: H361d - Suspected of damaging the unborn child. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.</p>
Precautionary Statement: Prevention	<p>P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
Precautionary Statement: Response	<p>P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER/doctor/ //if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to licensed waste disposal site</p>

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Highways PM04 Resin Solution

Revision 13
Revision date 2023-09-27

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Styrenes (Styrene)		100-42-5	202-851-5		40 - 50%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; STOT SE 3: H335; Repr. 2: H361d; STOT RE 1: H372; Aquatic Chronic 3: H412;
4-napthoquinone		130-15-4	204-977-6		0 - 0.5%	Acute Tox. 3: H301; Acute Tox. 3: H311; Skin Corr. 1C: H314; Skin Sens. 1: H317; Acute Tox. 1: H330; STOT SE 3: H335; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	. Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

Highways PM04 Resin Solution

Revision 13
Revision date 2023-09-27

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Highways PM04 Resin Solution (Larcrete PM Pt B)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Styrenes (Styrene)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 430
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 1080
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.





Exposure Pattern - Workers

Highways PM04 Resin Solution	Acute inhalation - Systemic effects	289 mg/m ³	
	Acute inhalation - Local effects	306 mg/m ³	Long-term - inhalation - Systemic effects
	Long-term - dermal - Systemic effects	406 mg/kg	

Exposure Pattern - General population

Highways PM04 Resin Solution	Acute inhalation - Systemic effects	174.25 mg/m ³	
	Acute inhalation - Local effects	182.75 mg/m ³	Long-term - inhalation - Systemic effects
	Long-term - dermal - Systemic effects	343 mg/kg	Long-term - oral - Systemic effects
			2.1 mg/kg

8.2. Exposure controls

	   
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

Highways PM04 Resin Solution

Revision 13
Revision date 2023-09-27

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber
Odour	Characteristic
Odour threshold	> 0.15 ppm
pH	7
Melting point	> 25 °C
Initial boiling point	145 °C
Flash point	33 °C
Upper Explosive Limit	6.1 %
Lower Explosive Limit	1.1 %
Vapour pressure	670 Pa
Relative Vapour Density	3.6 g/cm ³
Density / Relative Density	1.1 (H ₂ O = 1 @ 20 °C)
Partition coefficient (n-octanol/water)	> 2
Autoignition temperature	490 °C
Viscosity	> 0.205 x 10 ⁻⁶ m ² /s @ 40 °C (ISO 3104/3105)
Solubility	Insoluble in water

9.2. Other information

Specific gravity	1.05 - 1.2 g/cm ³
------------------	------------------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Harmful if inhaled. May be fatal if swallowed and enters airways.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause respiratory irritation.
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met).
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met).
Reproductive toxicity	Suspected of damaging the unborn child.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure .

11.1.4. Toxicological Information

Highways PM04 Resin Solution	Dermal Rat LD50: >2000mg/kg Inhalation Rat LC50/4 h: 10-20mg/L	Oral Rat LD50: >5000mg/kg
------------------------------	---	---------------------------

SECTION 12: Ecological information

12.1. Toxicity

Highways PM04 Resin Solution

Revision 13
Revision date 2023-09-27

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1866

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code F-E S-E

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

SECTION 16: Other information

Highways PM04 Resin Solution

Revision 13

Revision date 2023-09-27

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 1 - Other means of identification / UFI. 1 - UFI No. 11 - Acute toxicity. 11 - Skin corrosion/irritation. 11 - Respiratory or skin sensitisation. 11 - Germ cell mutagenicity. 11 - Carcinogenicity. 11 - Reproductive toxicity. 11 - Serious eye damage/irritation. 11 - STOT-single exposure. 11 - STOT-repeated exposure.
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Repr. 2: H361d - Suspected of damaging the unborn child. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. Acute Tox. 1: H330 - Fatal if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>
Further information	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>